

## TYRES

Product group	Tyres
Item number	17415920
Valid tyre size	600 / 60 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT



**NOKIAN®**  
**TYRES**

## Notes and features

- The tyre's wide contact area enables good lateral stability when unloading and high flotation on soft surfaces.
- The arrangement of the blocks with wide, angled spaces ensures good self-cleaning.
- Its special wear-resistant rubber compound was developed for operations on challenging ground such as rocky surfaces, as well as for road use.
- High-strength steel belt reinforcements combined with a cut- and crack-resistant rubber compound provide high puncture protection.
- The special construction of several steel plies allows high inflation pressures and increases the stability of the tyre.
- The asymmetrical arrangement of the blocks, which successively come into contact with the ground surface, reduces the noise generated when driving on the road.

## Technical Informations

Item number	17415920
EAN	6419440232775
Valid tyre size	600 / 60 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	207,75
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	610
Outer diameter of tyre [mm].	1496
Stat. radius (SLR) [mm]	681
Rolling circumference [mm].	4570
Tread depth (mm)	26,0
Tyre capacity 75% [litr.]	420
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		5,00	