Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	17416016	
Valid tyre size	750 / 55 - 26.5	
LI / SI / PR	189 A2 / 182 A8, 24 PR	
TL/TT	TT	
Brand	Nokian	
Tread pattern	Forest King F2	



Notes and features

- Robust and stable in challenging conditions in forests.
- Balanced shape and extremely high operational stability.
- Upright, rigid, hard-wearing sidewalls and robust tread.
- Effective puncture protection through steel inserts in the tread.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17416016
EAN	6419440455747
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	тт
Brand	Nokian
Tread pattern	Forest King F2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	284,55
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	750
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	674
Dynamic radius [mm]	714
Rolling circumference [mm].	4486
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 A2	10300	10		6,00	
182 A8	8500	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.