

TYRES

Product group	Tyres
Item number	17416060
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Forest King TRS 2



nokian®
TYRES

Notes and features

- Top-class innovation for forest construction sites with or without caterpillar tracks.
- The new shoulder construction improves the additional support for the bands and increases puncture resistance.
- Super Shovel - lug design improves the traction.
- New bead area with high resistance against rim slipping.
- Wide tread for low pressure on the soil.

Technical Informations

Item number	17416060
EAN	6419440455662
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Forest King TRS 2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	220,53
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	618
Dynamic radius [mm]	653
Rolling circumference [mm].	4103
Tyre capacity 75% [litr.]	490
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,00	
168 A8	5600	40		5,00	