

TYRES

Product group	Tyres
Item number	17416062
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Forest King TRS 2



nokian®
TYRES

Notes and features

- Top-class innovation for forest construction sites with or without caterpillar tracks.
- The new shoulder construction improves the additional support for the bands and increases puncture resistance.
- Super Shovel - lug design improves the traction.
- New bead area with high resistance against rim slipping.
- Wide tread for low pressure on the soil.

Technical Informations

Item number	17416062
EAN	6419440164366
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Forest King TRS 2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	272,83
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	750
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	674
Dynamic radius [mm]	716
Rolling circumference [mm].	4499
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 A2	10300	10		6,00	
182 A8	8500	40		6,00	