

## **TYRES**

Product group	Tyres	
Item number	17416064	
Valid tyre size	710 / 55 - 28.5	
LI / SI / PR	187 A2 / 180 A8, 24 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Forest King TRS 2	



## Notes and features

- Top-class innovation for forest construction sites with or without caterpillar tracks.
- The new shoulder construction improves the additional support for the bands and increases puncture resistance.
- Super Shovel lug design improves the traction.
- New bead area with high resistance against rim slipping.
- Wide tread for low pressure on the soil.



## **Technical Informations**

Item number	17416064
EAN	6419440216232
Valid tyre size	710 / 55 - 28.5
LI / SI / PR	187 A2 / 180 A8, 24 PR
TL/TT	тт
Brand	Nokian
Tread pattern	Forest King TRS 2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	280,10
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	710
Outer diameter of tyre [mm].	1525
Stat. radius (SLR) [mm]	693
Dynamic radius [mm]	735
Rolling circumference [mm].	4618
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
187 A2	9750	10		6,00	
180 A8	8000	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.