Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	17416112	
Valid tyre size	710 / 70 - 34	
LI / SI / PR	189 A2 / 181 A8, 24 PR	
TL/TT	TT	
Brand	Nokian	
Tread pattern	Forest King TRS 2+	



Notes and features

- The Nokian Forest King TRS 2+ is a forestry tyre, especially for 6-wheel forestry machines.
- The tyre provides excellent ground contact without chains and tracks and prevents soil damage.
- It can be perfectly combined with chains and tracks and supports their function optimally.
- The deep tread pattern with extra lugs in the shoulder area enables perfect chain contact and prevents damage to the tyre when operating with chains.
- An additional rubber ply on the tyre shoulder and steel reinforcements on the tread protect the tyre from damage caused by cuts and piercing.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17416112
EAN	6419440400075
Valid tyre size	710 / 70 - 34
LI / SI / PR	189 A2 / 181 A8, 24 PR
TL/TT	ТТ
Brand	Nokian
Tread pattern	Forest King TRS 2+
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	340,27
Recommended rim size	DW24B
Permitted rim size	DW23B
Maximum air pressure [bar].	4,00
Section width (mm)	754
Outer diameter of tyre [mm].	1833
Stat. radius (SLR) [mm]	819
Rolling circumference [mm].	5548
Tread depth (mm)	53,0
Tyre capacity 75% [ltr.]	675
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 A2	10300	10		4,00	
181 A8	8250	40		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.