

TYRES

Product group	Tyres
Item number	17421950
Valid tyre size	24.5 - 32
LI / SI / PR	169 A6, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2



Notes and features

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions.
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages.
- The particularly hard-wearing rubber compound is ideal for demanding forestry use.
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange.
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum.

Technical Informations

Item number	17421950
EAN	6419440219714
Valid tyre size	24.5 - 32
LI / SI / PR	169 A6, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	333,21
Recommended rim size	21
Maximum air pressure [bar].	3,10
Section width (mm)	622
Outer diameter of tyre [mm].	1831
Stat. radius (SLR) [mm]	835
Rolling circumference [mm].	5454
Tread depth (mm)	58,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	615
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A6	5800	30		2,80	
	8200	10		3,10	