

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 17421960 |
| Valid tyre size | 30.5 L - 32 |
| LI / SI / PR | 170 A6, 20 PR |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Logger King LS-2 |



Notes and features

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions.
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages.
- The particularly hard-wearing rubber compound is ideal for demanding forestry use.
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange.
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 17421960 |
| EAN | 6419440231143 |
| Valid tyre size | 30.5 L - 32 |
| LI / SI / PR | 170 A6, 20 PR |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Logger King LS-2 |
| TRA Code | LS-2 |
| Carcass properties | SF |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 409,22 |
| Recommended rim size | 27 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 775 |
| Outer diameter of tyre [mm]. | 1847 |
| Stat. radius (SLR) [mm] | 824 |
| Rolling circumference [mm]. | 5529 |
| Tread depth (mm) | 67,0 |
| Number of lugs | 16x2 |
| Tyre capacity 75% [ltr.] | 780 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 A6 | 6000 | 30 | | 2,10 | |
| | 8400 | 10 | | 2,40 | |