

## TYRES

Product group	Tyres
Item number	17421970
Valid tyre size	35.5 L - 32
LI / SI / PR	183 A6, 26 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2



## Notes and features

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions.
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages.
- The particularly hard-wearing rubber compound is ideal for demanding forestry use.
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange.
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum.

## Technical Informations

Item number	17421970
EAN	6419440231112
Valid tyre size	35.5 L - 32
LI / SI / PR	183 A6, 26 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	629,12
Recommended rim size	31
Maximum air pressure [bar].	2,80
Section width (mm)	902
Outer diameter of tyre [mm].	2011
Stat. radius (SLR) [mm]	902
Rolling circumference [mm].	6032
Tread depth (mm)	67,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	1120
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A6	8750	30		2,40	
	12250	10		2,80	