

TYRES

Product group	Tyres	
Item number	17422780	
Valid tyre size	18.4 - 38	
LI / SI / PR	155 A8, 14 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	TR Forest	



Notes and features

- Reliable tyre for agricultural tractors used in forestry.
- The right choice for tractors used predominantly for forest work.
- Reliable, versatile and optimally geared to the vehicle type.
- Special rubber compound for use in forest cultivation.
- Strong bias construction.
- Good on- and off-road handling.
- Soil-protecting, self-cleaning tread pattern.



Technical Informations

Item number	17422780
EAN	6419440854304
Valid tyre size	18.4 - 38
LI / SI / PR	155 A8, 14 PR
TL/TT	тт
Brand	Nokian
Tread pattern	TR Forest
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	156,99
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,60
Section width (mm)	467
Outer diameter of tyre [mm].	1750
Stat. radius (SLR) [mm]	819
Rolling circumference [mm].	5150
Tyre capacity 75% [ltr.]	385
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.