

TYRES

Product group	Tyres
Item number	17425995
Valid tyre size	250 / 75 R 16
LI / SI / PR	120 G
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Bohnenkamp
Moving Professionals

Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

Technical Informations

Item number	17425995
EAN	6419440060576
Valid tyre size	250 / 75 R 16
LI / SI / PR	120 G
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	21,00
Recommended rim size	8
Permitted rim size	W7, 7, 7J, W8, 8J, W9, 9, 9J
Maximum air pressure [bar].	4,50
Section width (mm)	258
Outer diameter of tyre [mm].	783
Stat. radius (SLR) [mm]	363
Speed Radius Index (SRI)	370
Rolling circumference [mm].	2390
Tread depth (mm)	16,0
Tyre capacity 75% [ltr.]	47.00
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 G	1400	90		4,50	