Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	17426015
Valid tyre size	360 / 70 R 20
LI / SI / PR	136 A8 / 131 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Notes and features

- Ideal in the most varying conditions, reliable throughout • the whole year.
- High level of directional stability in on-road and off-road • applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability. .
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17426015
EAN	6419440119861
Valid tyre size	360 / 70 R 20
LI / SI / PR	136 A8 / 131 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	59,92
Recommended rim size	W11
Permitted rim size	W10, W12
Maximum air pressure [bar].	3,20
Section width (mm)	341
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	470
Speed Radius Index (SRI)	500
Rolling circumference [mm].	3104
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	116.25
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40		3,20	
131 D	1950	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.