

TYRES

Product group	Tyres	
Item number	17426085	
Valid tyre size	340 / 80 R 24	
LI / SI / PR	140 A8 / 135 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	TRI 2	



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.



Technical Informations

Item number	17426085
EAN	6419440453767
Valid tyre size	340 / 80 R 24
Alternative size 1	12.4R24
LI / SI / PR	140 A8 / 135 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	69,64
Recommended rim size	DW11
Permitted rim size	W10, W11, W12, DW10, DW12
Maximum air pressure [bar].	3,20
Section width (mm)	330
Outer diameter of tyre [mm].	1154
Stat. radius (SLR) [mm]	521
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3487
Tread depth (mm)	25,0
Tyre capacity 75% [ltr.]	135
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		3,20	
135 D	2180	65		3,20	