

TYRES

Product group	Tyres
Item number	17426160
Valid tyre size	500 / 65 R 24
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus



Notes and features

- Designed as a radial all-round tyre for tractors in forestry use under normal stress on easy terrain, for lighter applications.
- Rugged and versatile.
- Good grip, highly-suited for road use.
- For comfortable, fast journeys.
- Soil-protecting, self-cleaning tread pattern.

Technical Informations

Item number	17426160
EAN	6419440454108
Valid tyre size	500 / 65 R 24
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	107,96
Recommended rim size	15
Permitted rim size	13, 14, 16
Maximum air pressure [bar].	2,40
Section width (mm)	480
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	575
Dynamic radius [mm]	594
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3735
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		2,40	
139 B	2430	50		2,40	