

TYRES

Product group	Tyres
Item number	17426190
Valid tyre size	420 / 65 R 24
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Bohnenkamp
Moving Professionals

Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

Technical Informations

Item number	17426190
EAN	6419440453927
Valid tyre size	420 / 65 R 24
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	80,93
Recommended rim size	DW13
Permitted rim size	W12, DW12, W13, W14L, DW14L, DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	402
Outer diameter of tyre [mm].	1155
Stat. radius (SLR) [mm]	525
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3493
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	165.00
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		4,00	
146 D	3000	65		4,00	