

TYRES

Product group	Tyres
Item number	17426200
Valid tyre size	460 / 65 R 24
LI / SI / PR	156 A8 / 151 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI Steel



Notes and features

- Ideal for landfills and frequent use of anti-skid chains.
- Super puncture resistant: extra strong reinforcement against cuts and punctures.
- Wide contact area and lug tread pattern for all surfaces.
- For tractors, wheel loaders and telescopic loaders.
- Effective puncture protection through steel inserts in the tread.

Technical Informations

Item number	17426200
EAN	6419440452456
Valid tyre size	460 / 65 R 24
LI / SI / PR	156 A8 / 151 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	97,72
Recommended rim size	13
Permitted rim size	14, 15
Maximum air pressure [bar].	4,00
Section width (mm)	437
Outer diameter of tyre [mm].	1185
Stat. radius (SLR) [mm]	545
Rolling circumference [mm].	3620
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		4,00	
151 D	3450	65		4,00	