

TYRES

Product group	Tyres
Item number	17426210
Valid tyre size	480 / 65 R 24
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI Steel



Notes and features

- Ideal for landfills and frequent use of anti-skid chains.
- Super puncture resistant: extra strong reinforcement against cuts and punctures.
- Wide contact area and lug tread pattern for all surfaces.
- For tractors, wheel loaders and telescopic loaders.
- Effective puncture protection through steel inserts in the tread.

Technical Informations

Item number	17426210
EAN	6419440452227
Valid tyre size	480 / 65 R 24
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI Steel
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	110,82
Recommended rim size	14
Permitted rim size	15, 16
Maximum air pressure [bar].	3,20
Section width (mm)	470
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	565
Rolling circumference [mm].	3740
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,20	
146 D	3000	65		3,20	