

TYRES

Product group	Tyres
Item number	17426212
Valid tyre size	540 / 65 R 24
LI / SI / PR	158 A8 / 154 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Bohnenkamp
Moving Professionals

Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

Technical Informations

Item number	17426212
EAN	6419440454207
Valid tyre size	540 / 65 R 24
LI / SI / PR	158 A8 / 154 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,77
Recommended rim size	DW18L
Permitted rim size	DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	582
Outer diameter of tyre [mm].	1311
Stat. radius (SLR) [mm]	582
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3965
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	311.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		3,20	
154 D	3750	65		3,20	