

## TYRES

Product group	Tyres
Item number	17426275
Valid tyre size	400 / 80 R 28
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Bohnenkamp  
Moving Professionals

## Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

## Technical Informations

Item number	17426275
EAN	6419440453835
Valid tyre size	400 / 80 R 28
Alternative size 1	14.9R28
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	100,56
Recommended rim size	DW13
Permitted rim size	W12, W13, W14L, DW12, DW14L
Maximum air pressure [bar].	3,20
Section width (mm)	397
Outer diameter of tyre [mm].	1351
Stat. radius (SLR) [mm]	620
Dynamic radius [mm]	649
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4078
Tread depth (mm)	27,0
Tyre capacity 75% [ltr.]	221.25

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,20	
146 D	3000	65		3,20	