

TYRES

Product group	Tyres
Item number	17426300
Valid tyre size	500 / 65 R 28
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus



Notes and features

- Designed as a radial all-round tyre for tractors in forestry use under normal stress on easy terrain, for lighter applications.
- Rugged and versatile.

- Good grip, highly-suited for road use.
- For comfortable, fast journeys.
- Soil-protecting, self-cleaning tread pattern.



Technical Informations

Item number	17426300
EAN	6419440454115
Valid tyre size	500 / 65 R 28
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	121,59
Recommended rim size	15
Permitted rim size	13, 14, 16
Maximum air pressure [bar].	2,40
Section width (mm)	480
Outer diameter of tyre [mm].	1347
Stat. radius (SLR) [mm]	622
Dynamic radius [mm]	645
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4055
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		2,40	
141 B	2575	50		2,40	