

TYRES

Product group	Tyres
Item number	17426405
Valid tyre size	440 / 80 R 30
LI / SI / PR	157 A8 / 153 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

Technical Informations

Item number	17426405
EAN	6419440453842
Valid tyre size	440 / 80 R 30
Alternative size 1	16.9R30
LI / SI / PR	157 A8 / 153 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	116,18
Recommended rim size	DW14L
Permitted rim size	DW15L, W16L
Maximum air pressure [bar].	3,20
Section width (mm)	430
Outer diameter of tyre [mm].	1464
Stat. radius (SLR) [mm]	660
Dynamic radius [mm]	708
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4448
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	288.75

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		3,20	
153 D	3650	65		3,20	