

## TYRES

Product group	Tyres
Item number	17426450
Valid tyre size	540 / 65 R 30
LI / SI / PR	161 A8 / 156 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

## Technical Informations

Item number	17426450
EAN	6419440453712
Valid tyre size	540 / 65 R 30
LI / SI / PR	161 A8 / 156 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	145,02
Recommended rim size	DW18L
Permitted rim size	DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	530
Outer diameter of tyre [mm].	1460
Stat. radius (SLR) [mm]	644
Dynamic radius [mm]	700
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4401
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	352.50
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		3,20	
156 D	4000	65		3,20	