

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 17426550 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 157 A8 / 154 B, 14 PR |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | TR Multiplus |



Notes and features

- Designed as a radial all-round tyre for tractors in forestry use under normal stress on easy terrain, for lighter applications.
- Rugged and versatile.
- Good grip, highly-suited for road use.
- For comfortable, fast journeys.
- Soil-protecting, self-cleaning tread pattern.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 17426550 |
| EAN | 6419440454139 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 157 A8 / 154 B, 14 PR |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | TR Multiplus |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 199,80 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 575 |
| Outer diameter of tyre [mm]. | 1644 |
| Stat. radius (SLR) [mm] | 750 |
| Rolling circumference [mm]. | 4930 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 157 A8 | 4125 | 40 | | 2,40 | |
| 154 B | 3750 | 50 | | 2,40 | |