

## TYRES

Product group	Tyres
Item number	17426620
Valid tyre size	500 / 65 R 28
LI / SI / PR	150 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King



## Notes and features

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites.
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear.
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface.
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre.
- The tyre can be fitted with spikes and driven with tyre chains.
- It provides high loading capacities at speeds up to 65 km/h.

## Technical Informations

Item number	17426620
EAN	6419440394190
Valid tyre size	500 / 65 R 28
LI / SI / PR	150 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King
TRA Code	R1
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	156,09
Recommended rim size	DW16L
Permitted rim size	DW15L, TW15L, TW16L, DW18L, TW18L
Maximum air pressure [bar].	3,20
Section width (mm)	503
Outer diameter of tyre [mm].	1361
Stat. radius (SLR) [mm]	629
Dynamic radius [mm]	653
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4103
Tread depth (mm)	48,0
Tyre capacity 75% [ltr.]	250
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 D	3350	65		3,20	