

## TYRES

Product group	Tyres
Item number	17426630
Valid tyre size	540 / 65 R 28
LI / SI / PR	154 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King



## Notes and features

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites.
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear.
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface.
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre.
- The tyre can be fitted with spikes and driven with tyre chains.
- It provides high loading capacities at speeds up to 65 km/h.

## Technical Informations

Item number	17426630
EAN	6419440351278
Valid tyre size	540 / 65 R 28
LI / SI / PR	154 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King
TRA Code	R1
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	180,19
Recommended rim size	DW18L
Permitted rim size	TL16L, TW18L
Maximum air pressure [bar].	3,20
Section width (mm)	550
Outer diameter of tyre [mm].	1413
Stat. radius (SLR) [mm]	650
Dynamic radius [mm]	676
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4248
Tread depth (mm)	49,0
Tyre capacity 75% [ltr.]	315
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		3,20	