

TYRES

Product group	Tyres
Item number	17426672
Valid tyre size	650 / 75 R 38
LI / SI / PR	175 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King



Notes and features

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites.
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear.
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface.
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre.
- The tyre can be fitted with spikes and driven with tyre chains.
- It provides high loading capacities at speeds up to 65 km/h.

Technical Informations

Item number	17426672
EAN	6419440351230
Valid tyre size	650 / 75 R 38
LI / SI / PR	175 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	356,82
Recommended rim size	DW20B
Permitted rim size	TW20B, DW21B, TW21B, DW23B, TW21B
Maximum air pressure [bar].	3,20
Section width (mm)	645
Outer diameter of tyre [mm].	1941
Stat. radius (SLR) [mm]	925
Rolling circumference [mm].	5889
Tread depth (mm)	55,0
Tyre capacity 75% [litr.]	740
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 D	6900	65		3,20	