

TYRES

Product group	Tyres
Item number	17426820
Valid tyre size	650 / 65 R 38
LI / SI / PR	164 A8 / 160 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus



Notes and features

- Designed as a radial all-round tyre for tractors in forestry use under normal stress on easy terrain, for lighter applications.
- Rugged and versatile.
- Good grip, highly-suited for road use.
- For comfortable, fast journeys.
- Soil-protecting, self-cleaning tread pattern.

Technical Informations

Item number	17426820
EAN	6419440454153
Valid tyre size	650 / 65 R 38
LI / SI / PR	164 A8 / 160 B
TL/TT	TL
Brand	Nokian
Tread pattern	TR Multiplus
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	248,78
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	645
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	838
Dynamic radius [mm]	873
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5485
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		2,40	
160 B	4500	50		2,40	