

TYRES

Product group	Tyres
Item number	17426950
Valid tyre size	650 / 65 R 42
LI / SI / PR	176 A8 / 171 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

Technical Informations

Item number	17426950
EAN	6419440453903
Valid tyre size	650 / 65 R 42
Alternative size 1	20.8R42
LI / SI / PR	176 A8 / 171 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	269,01
Recommended rim size	DW20A
Permitted rim size	DW18L, DW23A
Maximum air pressure [bar].	3,20
Section width (mm)	617
Outer diameter of tyre [mm].	1913
Stat. radius (SLR) [mm]	848
Dynamic radius [mm]	922
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5791
Tread depth (mm)	33,0
Tyre capacity 75% [ltr.]	693.75

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		3,20	
171 D	6150	65		3,20	