

TYRES

Product group	Tyres	
Item number	17426960	
Valid tyre size	620 / 80 R 42	
LI / SI / PR	181 A8 / 177 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	TRI 2	



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.



Technical Informations

Item number	17426960
EAN	6419440455181
Valid tyre size	620 / 80 R 42
LI / SI / PR	181 A8 / 177 D
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	300,32
Recommended rim size	DW20B
Permitted rim size	DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	626
Outer diameter of tyre [mm].	2059
Stat. radius (SLR) [mm]	925
Dynamic radius [mm]	1001
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6289
Tread depth (mm)	35,0
Tyre capacity 75% [ltr.]	843.75
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,20	
177 D	7300	65		3,20	