

TYRES

Product group	Tyres
Item number	17427112
Valid tyre size	420 / 65 R 24
LI / SI / PR	146 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI





Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces.
 Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.



Technical Informations

Item number	17427112
EAN	6419440455860
Valid tyre size	420 / 65 R 24
LI / SI / PR	146 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	84,51
Recommended rim size	13
Maximum air pressure [bar].	4,00
Section width (mm)	418
Outer diameter of tyre [mm].	1156
Stat. radius (SLR) [mm]	525
Rolling circumference [mm].	3493
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 D	3000	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.