Bohnenkamp Moving Professionals

21.09.2024

TYRES

| Product group | Tyres |
|-----------------|-------------------|
| Item number | 17427140 |
| Valid tyre size | 400 / 80 R 28 |
| LI / SI / PR | 146 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |



Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 17427140 |
|------------------------------|-------------------|
| EAN | 6419440455846 |
| Valid tyre size | 400 / 80 R 28 |
| Alternative size 1 | 14.9R28 |
| LI / SI / PR | 146 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |
| M+S | M+S |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 103,72 |
| Recommended rim size | 13 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 404 |
| Outer diameter of tyre [mm]. | 1351 |
| Stat. radius (SLR) [mm] | 620 |
| Rolling circumference [mm]. | 4090 |
| Tread depth (mm) | 25,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 146 D | 3000 | 65 | | 3,20 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.