

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 17427160 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 156 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 17427160 |
| EAN | 6419440211701 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 156 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |
| M+S | M+S |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 141,61 |
| Recommended rim size | 18 |
| Permitted rim size | 16 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 550 |
| Outer diameter of tyre [mm]. | 1464 |
| Stat. radius (SLR) [mm] | 665 |
| Rolling circumference [mm]. | 4430 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 156 D | 4000 | 65 | | 3,20 | |