

## TYRES

|                 |                   |
|-----------------|-------------------|
| Product group   | Tyres             |
| Item number     | 17427224          |
| Valid tyre size | 360 / 80 R 20     |
| LI / SI / PR    | 143 D             |
| TL/TT           | TL                |
| Brand           | Nokian            |
| Tread pattern   | Hakkapeliitta TRI |



**nokian®**  
**TYRES**

## Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.

## Technical Informations

|                              |                   |
|------------------------------|-------------------|
| Item number                  | 17427224          |
| EAN                          | 6419440349640     |
| Valid tyre size              | 360 / 80 R 20     |
| LI / SI / PR                 | 143 D             |
| TL/TT                        | TL                |
| Brand                        | Nokian            |
| Tread pattern                | Hakkapeliitta TRI |
| M+S                          | M+S               |
| Carcass properties           | Steel Belted      |
| Antistatic                   | No                |
| Tyre colour                  | Black             |
| ECE regulation number        | not necessary     |
| Nettogewicht [kg] (gültig)   | 67,91             |
| Recommended rim size         | 11                |
| Maximum air pressure [bar].  | 4,00              |
| Section width (mm)           | 360               |
| Outer diameter of tyre [mm]. | 1093              |
| Stat. radius (SLR) [mm]      | 493               |
| Rolling circumference [mm].  | 3311              |
| Tread depth (mm)             | 24,0              |
| Tyre capacity 75% [ltr.]     | 135               |
| E-Ready                      | No                |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 D | 2725               | 65           |               | 4,00                     |              |