

TYRES

Product group	Tyres
Item number	17427424
Valid tyre size	650 / 65 R 34
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Nokian
Tread pattern	Ground King



Notes and features

- The Nokian Ground King is a tractor tyre for various applications for agricultural contractors.
- It combines high ride comfort during transfers or road journeys with good traction in the field and on building sites.
- The patented Hybrilug technology unites the best characteristics of agricultural and block tread pattern.
- The special tread pattern design with large ground contact area and sturdy rubber compound ensures a long service life for the tyre.
- The arrangement of the tread elements enables stability and good steering characteristics off-road as well as excellent handling on the road.
- High loading capacities enable use on heavy equipment.



Technical Informations

Item number	17427424
EAN	6419440427461
Valid tyre size	650 / 65 R 34
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Nokian
Tread pattern	Ground King
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	235,03
Recommended rim size	DW20B
Maximum air pressure [bar].	3,20
Section width (mm)	650
Outer diameter of tyre [mm].	1700
Stat. radius (SLR) [mm]	769
Rolling circumference [mm].	5173
Tread depth (mm)	55,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	542
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		3,20	
164 E	5000	70		3,20	