Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	17466253
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 J
TL/TT	TL
Brand	Nokian
Tread pattern	E-Truck Trailer



Notes and features

- The Nokian E-Truck Trailer is an all-season trailer tyre.
- The pattern with zigzag-shaped grooves provides good stability and prevents damages caused by small stones.
- The robust tyre shoulder and the evenly wearing tread guarantee a long service life for the tyre.
- On top of that, the tyre is characterised by good grip on main roads, low rolling resistance and low fuel consumption.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466253
EAN	6419440413501
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 J
TL/TT	TL
Brand	Nokian
Tread pattern	E-Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D
Wet grip	В
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	28,50
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	8,50
Section width (mm)	212
Outer diameter of tyre [mm].	776
Stat. radius (SLR) [mm]	363
Rolling circumference [mm].	2359
Tread depth (mm)	12,0

05.02.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

05.02.2025

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 J	2180	100	Single	8,50	
133 J	2060	100	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.