

TYRES

| Product group | Tyres | |
|-----------------|-----------------|--|
| Item number | 17466258 | |
| Valid tyre size | 235 / 75 R 17.5 | |
| LI / SI / PR | 143 / 141 J | |
| TL/TT | TL | |
| Brand | Nokian | |
| Tread pattern | E-Truck Trailer | |



Notes and features

- The Nokian E-Truck Trailer is an all-season trailer tyre.
- The pattern with zigzag-shaped grooves provides good stability and prevents damages caused by small stones.
- The robust tyre shoulder and the evenly wearing tread guarantee a long service life for the tyre.
- On top of that, the tyre is characterised by good grip on main roads, low rolling resistance and low fuel consumption.



Technical Informations

| Item number | 17466258 |
|------------------------------|-----------------|
| EAN | 6419440368313 |
| Valid tyre size | 235 / 75 R 17.5 |
| LI / SI / PR | 143 / 141 J |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | E-Truck Trailer |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | С |
| Wet grip | A |
| Rolling noise [db]. | 69 |
| Rolling noise level | A |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 32,10 |
| Recommended rim size | 6.75 |
| Permitted rim size | 7.50 |
| Maximum air pressure [bar]. | 8,75 |
| Section width (mm) | 238 |
| Outer diameter of tyre [mm]. | 805 |
| Stat. radius (SLR) [mm] | 375 |
| Rolling circumference [mm]. | 2447 |
| Tread depth (mm) | 13,0 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





| E-Ready | No |
|---------|----|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 143 J | 2725 | 100 | Single | 8,75 | |
| 141 J | 2575 | 100 | Twin | 8,75 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.