Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	17466303
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	143 / 141 J
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Trailer



Notes and features

- The Nokian R-Truck Trailer is an all-season truck trailer tyre for mixed use on roads and building sites, caravans and forestry trailers.
- Its non-directional tread pattern with coarse tread blocks offers good on-road performance and good off-road selfcleaning properties.
- Its cut-resistant rubber compound protects the tyre from damages on difficult surfaces.
- The design of the main grooves with stone ejectors prevents small stones from penetrating the tyre and thus reduces the risk of punctures.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466303
EAN	6419440351445
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	143 / 141 J
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	E
Wet grip	В
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,70
Recommended rim size	7.50
Permitted rim size	6.75, 8.25
Maximum air pressure [bar].	8,50
Section width (mm)	252
Outer diameter of tyre [mm].	877
Stat. radius (SLR) [mm]	405
Rolling circumference [mm].	2666
Tread depth (mm)	15,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

15.11.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	8,50	
141 J	2575	100	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.