

TYRES

Product group	Tyres	
Item number	17466317	
Valid tyre size	275 / 70 R 22.5	
LI / SI / PR	148 / 145 K	
TL/TT	TL	
Brand	Nokian	
Tread pattern	R-Truck Trailer	



Notes and features

- The Nokian R-Truck Trailer is an all-season truck trailer tyre for mixed use on roads and building sites, caravans and forestry trailers.
- Its non-directional tread pattern with coarse tread blocks offers good on-road performance and good off-road selfcleaning properties.
- Its cut-resistant rubber compound protects the tyre from damages on difficult surfaces.
- The design of the main grooves with stone ejectors prevents small stones from penetrating the tyre and thus reduces the risk of punctures.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.



Technical Informations

Item number	17466317
EAN	6419440351421
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D
Wet grip	В
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,60
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	9,00
Section width (mm)	273
Outer diameter of tyre [mm].	972
Stat. radius (SLR) [mm]	451
Rolling circumference [mm].	2955
Tread depth (mm)	16,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 K	3150	110	Single	9,00	
145 K	2900	110	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.