Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	17466318
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 L
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck Trailer



Technical Informations

Item number	17466318
EAN	6419440511306
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 L
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Wet grip	C
Rolling noise [db].	68
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	54,50
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	9,00
Section width (mm)	273
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2945
Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 L	3150	120	Single	9,00	
145 L	2900	120	Twin	9,00	