Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	17466319	
Valid tyre size	275 / 70 R 22.5	
LI / SI / PR	148 / 145 M	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Hakkapeliitta Truck E2	



Notes and features

- The Nokian Hakkapeliitta Truck F2 is a winter tyre for the steer axle for regional and long-haul transport.
- The tyre provides excellent handling and braking behaviour, even in extreme wintry conditions.
- Deep zigzag-shaped grooves and the tyre's new shoulder design ensure good self-cleaning, especially on snowcovered roads.
- Spiral-shaped sipes remain reliably effective, even when the tyre is beginning to wear.
- Stone ejectors prevent small stones from penetrating and thus protect the tyre from damage.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466319
EAN	6419440511313
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta Truck E2
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	54,50
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	9,00
Section width (mm)	266
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2945
Tread depth (mm)	17,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

15.11.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 M	3150	130	Single	9,00	
145 M	2900	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.