

TYRES

Product group	Tyres	
Item number	17466338	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 148 M	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Hakkapeliitta Truck D	



Notes and features

- The Nokian Hakkapeliitta Truck D is a winter drive wheel tyre for long-haul transport.
- Its special tread pattern with twin blocks provides very good grip and high driving stability in all weather conditions, especially on compacted snow or icy road surfaces.
- The even tread block distribution and flat contact area ensure even wear.
- Siping activators boost the operation of the sipes in changing weather conditions.
- The deep 3D sipes guarantee a very good grip over the entire life cycle of the tyre, even with incipient wear.
- The tyre is characterised by low rolling resistance and low noise.
- It is equipped with DSI (Driving Safety Indication) which reliably indicates the remaining tread on the tyre.



Technical Informations

Item number	17466338
EAN	6419440123950
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta Truck D
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,00
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	296
Outer diameter of tyre [mm].	1063
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	1063
Tread depth (mm)	20,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	100	Single	8,50	
148 M	3150	130	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.