

## **TYRES**

Product group	Tyres
Item number	17466339
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta Truck E



## Notes and features

- The Nokian Hakkapeliitta Truck E is a truck drive wheel tyre for extremely adverse weather conditions.
- Its innovative tread pattern design with a network of more than 1,100 cross sipes provides maximum grip.
- The tread blocks, arranged in an arrow shape and with sharp leading edges, guarantee very good traction and braking properties, even on ice and snow.
- The staggered tread block arrangement makes the tyre particularly quiet.
- Due to a special rubber compound, the tyre is extremely wear resistant and retains its good handling characteristics in all weather conditions.
- The tyre is equipped with DSI (Driving Safety Indication) which reliably indicates the remaining tread on the tyre.



## **Technical Informations**

Item number	17466339
EAN	6419440750170
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta Truck E
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	Е
Wet grip	D
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,00
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	296
Outer diameter of tyre [mm].	1064
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3231
Tread depth (mm)	20,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	8,50	
148 M	3150	130	Twin	8,50	