# Bohnenkamp Moving Professionals

15.11.2024

### **TYRES**

Product group	Tyres
Item number	17466360
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	154 / 148 L
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck Steer



#### Notes and features

- The Nokian Hakka Truck Steer is an all-season tyre for local and long-distance transport.
- The wide groove tread pattern offers durability through even wear and good ride comfort.
- Sipe activators ensure good grip even on wet and slippery roads.
- The special tread pattern ejects small stones and protects the tyre from damages.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	17466360
EAN	6419440388731
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	154 / 148 L
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck Steer
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,40
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	314
Outer diameter of tyre [mm].	959
Stat. radius (SLR) [mm]	449
Rolling circumference [mm].	2915
Tread depth (mm)	13,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

15.11.2024

E-Ready

No

#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
148 L	3150	120	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.