

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 17466361 |
| Valid tyre size | 315 / 60 R 22.5 |
| LI / SI / PR | 152 / 148 L |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakka Truck Drive |

Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Nokian Hakka Truck Drive is an all-season tyre for drive axles for regional and long-distance transport.
- Its open V-shaped tread pattern with efficient sipes provides a secure grip in wintry conditions and good self-cleaning properties.
- The tyre wears evenly and has a long service life.
- It is equipped with DSI (Driving Safety Indication), which reliably indicates the remaining tread on the tyre.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 17466361 |
| EAN | 6419440388755 |
| Valid tyre size | 315 / 60 R 22.5 |
| LI / SI / PR | 152 / 148 L |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakka Truck Drive |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | RA |
| Rolling resistance | C |
| Wet grip | C |
| Rolling noise [db]. | 76 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 58,70 |
| Recommended rim size | 9.00 |
| Permitted rim size | 9.75 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 311 |
| Outer diameter of tyre [mm]. | 963 |
| Stat. radius (SLR) [mm] | 450 |
| Rolling circumference [mm]. | 2927 |
| Tread depth (mm) | 15,5 |

| | |
|---------|----|
| E-Ready | No |
|---------|----|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 L | 3550 | 120 | Single | 9,00 | |
| 148 L | 3150 | 120 | Twin | 9,00 | |