Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	17466374	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	R 154 / 150 L (152 / 148 M)	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Hakkapeliitta Truck E2	



Technical Informations

Item number	17466374
EAN	6419440427492
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	154 / 150 L (152 / 148 M)
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta Truck E2
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Wet grip	D
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	66,70
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	314
Outer diameter of tyre [mm].	1027
Stat. radius (SLR) [mm]	474
Rolling circumference [mm].	3122
Tread depth (mm)	18,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
152 M	3550	130	Single	9,00	
150 L	3350	120	Twin	9,00	
				9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.