

## **TYRES**

Product group	Tyres	
Item number	17466404	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 K	
TL/TT	TL	
Brand	Nokian	
Tread pattern	R-Truck Drive	



## Notes and features

- The Nokian R-Truck Drive is a truck tyre for the drive axle for year-round use in various conditions, on construction sites, forest paths and asphalted roads.
- The non-directional, open tread pattern has good selfcleaning properties and provides excellent grip in changing driving conditions.
- Large tread blocks reduce material separation and the formation of cracks.
- Stone ejectors in the main grooves prevent the penetration of small stones.
- The low heat development during road use enables even wear and a long service life for the tyre.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.



## **Technical Informations**

Item number	17466404
EAN	6419440314549
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Drive
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	75
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,00
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,25
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3271
Tread depth (mm)	21,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No
------------

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,25	
150 K	3350	110	Twin	8,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.