

TYRES

Product group	Tyres	
Item number	17466406	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 K	
TL/TT	TL	
Brand	Nokian	
Tread pattern	R-Truck Steer	



Notes and features

- The Nokian R-Truck Steer is a truck steering axle tyre for year-round use in various conditions, on construction sites, forest paths and asphalted roads.
- The non-directional, open tread pattern ensures good self-cleaning and slow wear.
- Stone ejectors prevent small stones from penetrating on unpaved surfaces and thus extend the service life of the tyre.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.



Technical Informations

Item number	17466406
EAN	6419440314556
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Steer
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С
Wet grip	В
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	65,00
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,25
Section width (mm)	309
Outer diameter of tyre [mm].	1082
Stat. radius (SLR) [mm]	503
Rolling circumference [mm].	3289
Tread depth (mm)	16,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,25	
150 K	3350	110	Twin	8,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.