Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	17466430
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck 844



Notes and features

- The Nokian Hakka Truck 844 is an all-season tyre for regional and long-distance transport.
- It is suitable for use as a trailer and semi-trailer tyre, but can also be used on the steering axle.
- It is marked with the Alpine symbol and offers very good performance, even in wintry conditions.
- The rib pattern ejects small stones due to its structure and ensures a long service life for the tyre.
- The tyre is equipped with DSI (Driving Safety Indication), which reliably indicates the remaining tread.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466430
EAN	6419440143439
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	ть
Brand	Nokian
Tread pattern	Hakka Truck 844
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	72,00
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	384
Outer diameter of tyre [mm].	1002
Stat. radius (SLR) [mm]	467
Rolling circumference [mm].	3046
Tread depth (mm)	15,0

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.