Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	17466434	
Valid tyre size	385 / 55 R 22.5	
LI / SI / PR	160 K (158 L)	
TL/TT	TL	
Brand	Nokian	
Tread pattern	E-Truck Trailer	



Notes and features

- The Nokian E-Truck Trailer is an all-season trailer tyre.
- The pattern with zigzag-shaped grooves provides good stability and prevents damages caused by small stones.
- The robust tyre shoulder and the evenly wearing tread guarantee a long service life for the tyre.
- On top of that, the tyre is characterised by good grip on main roads, low rolling resistance and low fuel consumption.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466434
EAN	6419440269887
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Nokian
Tread pattern	E-Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	C
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	74,20
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	384
Outer diameter of tyre [mm].	1000
Stat. radius (SLR) [mm]	466
Rolling circumference [mm].	3040
Tread depth (mm)	14,5

21.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

21.09.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.