Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	17466447
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Steer



Notes and features

- The Nokian R-Truck Steer is a truck steering axle tyre for year-round use in various conditions, on construction sites, forest paths and asphalted roads.
- The non-directional, open tread pattern ensures good self-cleaning and slow wear.
- Stone ejectors prevent small stones from penetrating on unpaved surfaces and thus extend the service life of the tyre.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17466447
EAN	6419440328584
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Steer
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	В
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	75,00
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	378
Outer diameter of tyre [mm].	1086
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3301
Tread depth (mm)	16,0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



15.11.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.